

10BASE-T/ETHERNET ISOLATION TRANSFORMER

Turns Ratio ($\pm 5\%$)

1:1

TRIPLE STYLE

(3 Transformers per Package)

IEEE 802.3 (10 BASE 2, 10 BASE 5)
& ECMA Compatible

Flammability: Materials used in the production of these units meet requirements of UL94-VO and IEC 695-2-2 needle flame test.

Parts shipped in anti-static tubes. 19 pieces per tube

Surface mount version of this part available. Part# T-10902G

PARAMETER	MIN.	MAX.	UNITS
Open Circuit Inductance	40	60	μHy
Leakage Inductance		0.2	μHy
Interwinding Capacitance ($C_{w/w}$)		9	pF
Rise Time		3	ns
ET	2.1		V μS
Primary DC Resistance		0.2	ohms
Secondary DC Resistance		0.2	ohms
High Potential Test	2000		V _{RMS}


Test Conditions:

Oscillation Voltage = 20mV


Oscillation Frequency = 100.0 KHz

PHYSICAL DIMENSIONS

All dimensions in inches (mm):



SCHEMATIC DIAGRAM:



RHOMBUS P/N: **T-10902**

CUST P/N:

NAME:

DATE: 07/02/98

SHEET: 1 OF 1