

10BASE-T/ETHERNET ISOLATION TRANSFORMER

Turns Ratio (±5%)	1:1
---------------------	-----

TRIPLE STYLE
(3 Transformers per Package)

PARAMETER	MIN.	MAX.	UNITS
Open Circuit Inductance	60	90	μHy
Leakage Inductance		0.2	μHy
Interwinding Capacitance ($C_{w/w}$)		10	pF
Rise Time		3	ns
ET	2.3		VμS
Primary DC Resistance		0.25	ohms
Secondary DC Resistance		0.25	ohms
High Potential Test	2000		V _{RMS}

IEEE 802.3 (10 BASE 2, 10 BASE 5)
& ECMA Compatible

Flammability: Materials used in the production of these units meet requirements of UL94-VO and IEC 695-2-2 needle flame test.


Parts shipped in anti-static tubes. 19 pieces per tube

Surface mount version of this part available. Part# T-10903G


Test Conditions:
Oscillation Voltage = 20mV
Oscillation Frequency = 100.0 KHz

PHYSICAL DIMENSIONS

All dimensions in inches (mm):



SCHEMATIC DIAGRAM:



RHOMBUS P/N: T-10903	
CUST P/N:	NAME:
DATE: 07/02/98	SHEET: 1 OF 1