

14 Pin 10-Tap TTL Buffered Delay Modules

OPERATING SPECIFICATIONS

V_{CC} Supply Voltage Commercial Grade 5.00±0.25 VDC
 V_{CC} Supply Voltage Military Grade 5.00±0.50 VDC
 I_{CC} Supply Current 120 mA typical
 Logic "1" Input: V_{IH} 2.00V min., 5.50V max.
 I_{IH} 50µA max. @ 2.4V
 Logic "0" Input: V_{IL} 0.80V max.
 I_{IL} -2mA max.
 V_{OH} Logic "1" Voltage Out 2.40V min.
 V_{OL} Logic "0" Voltage Out 0.50V max.
 T_{RO} Output Rise Time 4.00ns max.
 P_{VI} Input Pulse Width 20% of total delay min.
 Operating Temperature Range Commercial Grade 0° to 70°C
 Operating Temperature Range Military Grade -55° to +125°C
 Storage Temperature Range -65° to +150°C

PART NUMBER DESCRIPTION

D2TZM1 - XXX X

14 Pin 10-Tap Schottky TTL Delay Module

Total Delay in nanoseconds (ns)

Grade

Blank = Commercial Grade
M = Military Grade


TEST CONDITIONS

(Measurements made at 25°C)

V_{CC} Supply Voltage 5.00VDC
 Input Pulse Voltage 3.20V
 Input Pulse Rise Time 3.00ns max.
 Input Pulse Period 5.0 x Total Delay
 Input Pulse Duty Cycle 50%
 10pF Load on Outputs

Part Number	Nominal Tap Delays (ns) ±5% or 2ns whichever is greater									OUTPUT (ns)	Tap-to-Tap (ns)
	1	2	3	4	5	6	7	8	9		
D2TZM1-10	5	6	7	8	9	10	11	12	13	14 ± 1.50	1 ± 0.5
D2TZM1-20	5	7	9	11	13	15	17	19	21	23 ± 1.50	2 ± 0.8
D2TZM1-50	5	10	15	20	25	30	35	40	45	50 ± 2.50	5 ± 2.0
D2TZM1-60	6	12	18	24	30	36	42	48	54	60 ± 3.00	6 ± 2.0
D2TZM1-70	7	14	21	28	35	42	49	56	63	70 ± 3.50	7 ± 2.0
D2TZM1-75	7.5	15	22.5	30	37.5	45	52.5	60	67.5	75 ± 3.75	7.5 ± 2.0
D2TZM1-80	8	16	24	32	40	48	56	64	72	80 ± 4.00	8 ± 2.0
D2TZM1-90	9	18	27	36	45	54	63	72	81	90 ± 4.50	9 ± 2.0
D2TZM1-100	10	20	30	40	50	60	70	80	90	100 ± 5.00	10 ± 2.0
D2TZM1-120	12	24	36	48	60	72	84	96	108	120 ± 6.00	12 ± 2.5
D2TZM1-150	15	30	45	60	75	90	105	120	135	150 ± 7.50	15 ± 3.0
D2TZM1-200	20	40	60	80	100	120	140	160	180	200 ± 10.00	20 ± 3.0
D2TZM1-250	25	50	75	100	125	150	175	200	225	250 ± 12.50	25 ± 3.0
D2TZM1-300	30	60	90	120	150	180	210	240	270	300 ± 15.00	30 ± 3.0
D2TZM1-350	35	70	105	140	175	210	245	280	315	350 ± 17.50	35 ± 4.0
D2TZM1-400	40	80	120	160	200	240	280	320	360	400 ± 20.00	40 ± 4.0
D2TZM1-500	50	100	150	200	250	300	350	400	450	500 ± 25.00	50 ± 5.0
D2TZM1-600	60	120	180	240	300	360	420	480	540	600 ± 30.00	60 ± 6.0
D2TZM1-1000	100	200	300	400	500	600	700	800	900	1000 ± 50.00	100 ± 10.0

SCHEMATIC DIAGRAM




1. Rise Times are measured from 0.75V to 2.40V
2. Delays measured 1.50V level of leading edge.
3. Delays change \approx 2% per 5% change in V_{CC} .

VARIATIONS AVAILABLE. FOR INTERMEDIATE VALUES AND/ OR CUSTOM DESIGNS PLEASE CONSULT THE FACTORY.

PHYSICAL DIMENSIONS

inches (mm)



Specifications subject to change without notice.

D2TZM1-10/94